

## ACETRON® LSG



POLYACETAL [POM-C]

Acetron® LSG natural/black

ROUND RODS					
Diameters [mm]	Tolerances on the diameters [mm]	Acetron® LSG natural		Acetron® LSG black	
		Standard length per piece: [3000 mm <sup>[1]</sup> ]			
		[kg/pce <sup>[2]</sup> ]		[kg/pce <sup>[2]</sup> ]	
6	+0,1 +0,4	0,14	□	0,14	□
8		0,24	□	0,24	□
10	+0,1 +0,5	<b>0,36</b>	■	<b>0,36</b>	■
12		0,53	□	0,53	□
14		0,71	□	0,71	□
15		0,81	□	0,81	□
16	+0,2 +0,7	0,92	□	0,92	□
18		1,16	□	1,16	□
20		<b>1,42</b>	■	<b>1,42</b>	■
22		1,73	□	1,73	□
25	+0,2 +0,9	<b>2,22</b>	■	<b>2,22</b>	■
28		2,78	□	2,78	□
30		3,18	□	3,18	□
32		3,63	□	3,63	□
36	+0,2 +1,1	4,56	□	4,56	□
40		<b>5,61</b>	■	<b>5,61</b>	■
45		7,11	□	7,11	□
50	+0,3 +1,3	<b>8,76</b>	■	<b>8,76</b>	■
56		10,95	□	10,95	□
60		12,60	□	12,60	□
65	+0,3 +1,6	14,76	□	14,76	□
70		17,07	□	17,07	□
75		19,71	□	19,71	□
80	+0,4 +2,0	22,38	□	22,38	□
90	+0,5 +2,2	28,29	□	28,29	□
100	+0,6 +2,5	34,95	□	34,95	□
110	+0,7 +3,0	42,45	□	42,45	□
120	+0,8 +3,5	50,70	□	50,70	□
130		59,40	□	59,40	□
140	+0,9 +3,8	68,70	□	68,70	□
150	+1,0 +4,2	79,05	□	79,05	□
160	+1,1 +4,5	90,00	□	90,00	□
170		101,70	□	101,70	□
180	+1,2 +5,0	113,70	□	113,70	□
190		126,90	□	126,90	□
200	+1,3 +5,5	140,40	□	140,40	□
Other standard length: [1000 mm <sup>[1][3]</sup> ]					

<sup>[1]</sup>: tolerances on width +5/25 mm, on length -0/+3 %

<sup>[2]</sup>: average production weights

<sup>[3]</sup>: non-standard size for thicknesses over 25 mm [manufactured to order and subject to special conditions]

■ : **standard** item [generally available from stock; bulk quantities to be manufactured to order]

▣ : **semi-standard** item [generally not available from stock, minimum order quantity 1 piece]

□ : **non-standard** item [generally not available from stock, manufactured to order and subject to special conditions; improved availability possible upon customer planning]