



POLYAMIDE [PA 4.6] [66-GF30]

Ertalon® 4.6

Ertalon® 66-GF30

ROUND RODS					
Diameters [mm]	Tolerances ^[1] on the diameters [mm]	Ertalon® 4.6		Ertalon® 66 – GF 30	
		Standard length per piece: [3000 mm ^[2]]			
		[kg/pce ^[3]]		[kg/pce ^[3]]	
10	+0,1 +0,5	–	–	0,33	■
12		–	–	0,49	■
15		–	–	0,75	■
16	+0,2 +0,7	0,77	■	0,85	■
18		0,97	□	1,07	□
20		1,19	■	1,31	■
22		1,44	□	1,59	□
25	+0,2 +0,9	1,85	■	2,04	■
28		2,31	□	2,55	□
30		2,64	■	2,91	■
32		3,03	□	3,33	□
36	+0,2 +1,1	3,81	□	4,20	■
40		4,71	■	5,16	■
45		5,97	□	6,54	■
50	+0,3 +1,3	7,35	■	8,04	■
60		10,56	■	11,58	■
70	+0,3 +1,6	–	–	15,66	■
80	+0,4 +2,0	–	–	20,52	■
90	+0,5 +2,2	–	–	25,98	□
100	+0,6 +2,5	–	–	32,10	■
110	+0,7 +3,0	–	–	39,00	□
120		–	–	46,50	■
125	+0,8 +3,5	–	–	50,40	□
130		–	–	54,60	□
140	+0,9 +3,8	–	–	63,15	□
150	+1,0 +4,2	–	–	72,60	■
180	+1,2 +5,0	–	–	104,55	■
200	+1,3 +5,5	–	–	128,85	■
Other standard length: [1000 mm ^[2]]					

^[1]: tolerances according to EN 15860

^[2]: tolerances on the length -0/+3%

^[3]: average production weight

■ : **standard** item [generally available from stock; bulk quantities to be manufactured to order]

■ : **semi-standard** item [generally not available from stock, minimum order quantity 1 piece]

□ : **non-standard** item [generally not available from stock, manufactured to order and subject to special conditions; improved availability possible upon customer planning]