

NYLATRON®

POLYAMIDE [PA 66 + MOS₂]

Nylatron® GS

ROUND RODS			
Diameters [mm]	Tolerances ^[1] on the diameters [mm]	Nylatron® GS	
		Standard length per piece: [3000 mm ^[2]] [kg/pce ^[3]]	
6	+0,1 +0,4	0,11	□
8	+0,1 +0,5	0,19	□
10		0,29	■
12	+0,2 +0,7	0,43	■
15		0,66	□
16		0,75	■
18		0,95	■
20	+0,2 +0,9	1,16	■
22		1,41	□
25		1,82	■
28	+0,2 +1,1	2,27	□
30		2,58	■
32		2,96	■
35	+0,3 +1,3	3,51	■
40		4,56	■
45		5,82	■
50		7,14	■
Other standard length: [1000 mm ^[2]]			

^[1]: tolerances according to EN 15860

^[2]: tolerances on the length -0/+3 %

^[3]: average production weight

- : **standard** item [generally available from stock; bulk quantities to be manufactured to order]
- ▣ : **semi-standard** item [generally not available from stock, minimum order quantity 1 piece]
- : **non-standard** item [generally not available from stock, manufactured to order and subject to special conditions; improved availability possible upon customer planning]