

# NYLATRON®

POLYAMIDE [PA 66 + MOS<sub>2</sub>]

Nylatron® GS

TUBES				
Diameters [mm]	Tolerances <sup>[1]</sup> on the diameters [mm]		Nylatron® GS	
	O.D. x I.D.	O.D.	I.D.	Standard length per piece: [3000 mm <sup>[2]</sup> ] [kg/pce <sup>[3]</sup> ]
20 x 10				0,98 □
25 x 15	+0,4 +1,1	-0,4 -1,1		1,30 □
30 x 15				<b>2,09</b> ■
30 x 20				1,62 □
36 x 20				<b>2,94</b> ■
36 x 25	+0,6 +2,0	-0,6 -2,0		2,37 □
40 x 25				<b>3,24</b> ■
40 x 30				2,52 □
45 x 25				4,44 □
45 x 30				3,75 □
45 x 35				2,88 □
50 x 30				5,10 □
50 x 35	+0,8 +2,5	-0,8 -2,5		4,23 □
50 x 40				3,24 □
60 x 45				5,49 □
60 x 50				4,23 □
65 x 50	+0,8 +3,0	-0,8 -3,0		6,18 □
65 x 55				4,80 □
66 x 53				5,76 □
Other standard length: [1000 mm <sup>[2]</sup> ]				

For non-listed intermediate diameter, please consult us!

<sup>[1]</sup>: tolerances according to EN 15860

<sup>[2]</sup>: tolerance on the length -0/+3%

<sup>[3]</sup>: average production weight

- : **standard** item [generally available from stock; bulk quantities to be manufactured to order]
- ▣ : **semi-standard** item [generally not available from stock, minimum order quantity 1 piece]
- : **non-standard** item [generally not available from stock, manufactured to order and subject to special conditions; improved availability possible upon customer planning]