

NYLATRON®



POLYAMIDE [PA6 + OIL]

Nylatron® LFG natural

Nylatron® LFG blue

ROUND RODS					
Diameters [mm]	Tolerances ^[1] on the diameters [mm]	Nylatron® LFG natural		Nylatron® LFG blue	
		Standard length per piece: [1000 mm ^[2]]			
		[kg/pce ^[3]]		[kg/pce ^[3]]	
160	+2,0 +7,0	24,59	□	24,59	□
170		27,67	□	27,67	□
180		30,93	□	30,93	□
190		34,38	□	34,38	□
200		38,00	□	38,00	□
210	+3,0 +9,0	42,40	□	42,40	□
220		46,41	□	46,41	□
225		48,49	□	48,49	□
230		50,61	□	50,61	□
240		54,99	□	54,99	□
250		59,56	□	59,56	□
260		64,30	□	64,30	□
270		69,22	□	69,22	□
275		71,76	□	71,76	□
280		74,33	□	74,33	□
290	79,62	□	79,62	□	
300	85,09	□	85,09	□	
325	+4,0 +11,0	100,47	□	100,47	□
350		116,15	□	116,15	□
375		132,96	□	132,96	□
400	+5,0 +13,0	150,91	□	150,91	□
425		171,17	□	171,17	□
450		191,46	□	191,46	□
475		212,89	□	212,89	□
500		235,45	□	235,45	□

Other standard length: [500 mm^[2]]

^[1]: tolerances according to EN 15860

^[2]: tolerances on the length -0/+3%

^[3]: average production weight

■ : **standard** item [generally available from stock; bulk quantities to be manufactured to order]

▣ : **semi-standard** item [generally not available from stock, minimum order quantity 1 piece]

□ : **non-standard** item [generally not available from stock, manufactured to order and subject to special conditions; improved availability possible upon customer planning]