

NYLATRON®

POLYAMIDE [PA 6] [PA 6 + MOS₂]

Nylatron® MC 901

Nylatron® GSM

ROUND RODS					
Diameters [mm]	Tolerances ^[1] on the diameters [mm]	Nylatron® MC 901		Nylatron® GSM	
		Standard length per piece: [3000 mm ^[2]]			
		[kg/pce ^[3]]		[kg/pce ^[3]]	
50	+0,5 +1,5	7,19	■	7,22	■
56		8,97	□	9,01	■
60	+0,5 +1,8	10,33	■	10,37	■
65		12,10	□	12,14	■
70	+0,7 +2,3	14,00	□	14,04	■
75		16,15	□	16,24	■
80	+1,0 +2,7	18,35	□	18,43	■
85		20,85	□	20,93	■
90	+1,0 +2,9	23,30	□	23,40	□
95		25,95	□	26,05	□
100	+1,0 +3,3	28,71	■	28,84	■
110		34,80	□	34,89	■
120	+1,1 +3,8	41,40	□	41,55	□
125		44,85	□	45,00	□
130	+1,2 +4,1	48,60	□	48,82	■
140		56,25	□	56,45	□
150	+1,3 +4,5	64,65	□	64,86	□
Other standard length: [1000 mm ^[2]]					
		Standard length per piece: [1000 mm ^[2]]			
[mm]	[mm]	[kg/pce ^[3]]		[kg/pce ^[3]]	
160	+2,0 +7,0	24,90	■	25,00	■
170		28,05	□	28,15	□
180	+2,0 +7,0	31,35	■	31,50	■
190		34,85	□	35,00	□
200	+3,0 +9,0	38,50	■	38,65	■
210		42,95	□	43,15	□
220	+3,0 +9,0	47,05	□	47,25	□
225		49,15	□	49,35	□
230	+3,0 +9,0	51,30	□	51,50	□
240		55,70	□	55,95	□
250	+3,0 +9,0	60,35	□	60,60	■
260		65,15	□	65,45	□
270	+4,0 +11,0	70,15	□	70,45	□
275		72,70	□	73,00	□
280	+4,0 +11,0	75,30	□	75,65	□
290		80,65	□	81,00	□
300	+4,0 +11,0	86,20	□	86,60	□
325		101,80	□	102,20	□
350	+4,0 +11,0	117,70	□	118,20	□
375		134,70	□	135,30	□
400	+5,0 +13,0	152,90	□	153,60	□
425		173,40	□	174,20	□
450	+5,0 +13,0	194,00	□	194,80	□
475		215,70	□	216,60	□
500	+5,0 +13,0	238,50	□	239,60	□
Other standard length: [500 mm ^[2]]					

^[1]: tolerances according to EN 15860^[2]: tolerances on the length -0/+3 %^[3]: average production weight■ : **standard** item [generally available from stock; bulk quantities to be manufactured to order]■ : **semi-standard** item [generally not available from stock, minimum order quantity 1 piece]□ : **non-standard** item [generally not available from stock, manufactured to order and subject to special conditions; improved availability possible upon customer planning]