

PC 1000



POLYCARBONATE [PC]

PC 1000 NATURAL

ROUND RODS			
Diameters [mm]	Tolerances ^[1] on the diameters [mm]	PC 1000 natural	
		Standard length per piece: [3000 mm ^[2]]	
		[kg/pce ^[3]]	
6	+0,1 +0,4	0,11	□
8		0,20	□
10	+0,1 +0,5	0,30	■
12		0,45	□
16	+0,2 +0,9	0,79	□
20		1,21	■
22		1,48	□
25		1,89	□
28	+0,2 +1,2	2,37	□
30		2,70	■
32		3,06	□
36		3,90	□
40	+0,2 +1,6	4,80	■
45		6,12	□
50	+0,3 +2,0	7,50	■
56		9,36	□
60		10,83	■
65	+0,3 +2,5	12,66	□
70		14,64	□
75		16,89	□
80	+0,4 +3,0	19,17	▣
90	+0,5 +3,4	24,27	□
100	+0,6 +3,8	29,97	■
110	+0,7 +4,2	36,30	□
120	+0,8 +4,6	43,20	□
125		46,80	□
130		50,85	□
140	+0,9 +5,4	58,80	□
150	+1,0 +5,8	67,50	□
160	+1,1 +6,3	76,95	□
170	+1,2 +7,4	87,15	□
180		97,50	□
190	+1,3 +8,5	109,05	□
200		120,45	▣
Other standard length: [1000 mm ^[2]]			

^[1]: tolerances according to DIN 16980

^[2]: tolerance on the length -0/+3%

^[3]: average production weight

■ : **standard** item [generally available from stock; bulk quantities to be manufactured to order]

▣ : **semi-standard** item [generally not available from stock, minimum order quantity 1 piece]

□ : **non-standard** item [generally not available from stock, manufactured to order and subject to special conditions; improved availability possible upon customer planning]