



STATIC DISSIPATIVE POLYACETAL [POM]

Semitron® ESd 225

ROUND RODS				
Diameters ^{[1][2]}		Standard lengths [mm ^[1]]	Semitron® ESd 225	
[mm]	[inch]		[kg / pce ^[3]]	
4,76	3/16	2440	0,06	□
6,35	1/4	2440	0,10	□
7,94	5/16	2440	0,16	□
9,53	3/8	2440	0,23	□
11,11	7/16	2440	0,32	□
12,70	1/2	2440	0,41	□
14,29	9/16	2440	0,53	□
15,88	5/8	2440	0,65	□
19,05	3/4	2440	0,93	□
22,23	7/8	2440	1,27	□
25,40	1	2440	1,64	□
28,58	1 1/8	2440	2,10	□
31,75	1 1/4	2440	2,59	□
34,93	1 3/8	2440	3,13	□
38,10	1 1/2	2440	3,73	□
41,28	1 5/8	2440	4,37	□
44,45	1 3/4	2440	5,07	□
47,63	1 7/8	2440	5,82	□
50,80	2	2440	6,63	□
53,98	2 1/8	2440	7,48	□
57,15	2 1/4	2440	8,39	□
63,50	2 1/2	2440	10,35	□
69,85	2 3/4	2440	12,55	□
76,20	3	1220	7,40	□
82,55	3 1/4	1220	8,75	□
88,90	3 1/2	1220	10,15	□
95,25	3 3/4	1220	11,65	□
101,60	4	1220	13,25	□

^[1]: all dimensions shown are minimum values

^[2]: for non-listed intermediate diameters, please consult us

^[3]: theoretical weights, based on nominal dimensions and average density

■ : **standard** item [generally available from stock; bulk quantities to be manufactured to order]

▣ : **semi-standard** item [generally not available from stock, minimum order quantity 1 piece]

□ : **non-standard** item [generally not available from stock, manufactured to order and subject to special conditions; improved availability possible upon customer planning]