

SYMALIT® PVDF 1000



POLYVINYLIDENE FLUORIDE [PVDF]

Symalit® PVDF 1000 natural

ROUND RODS			
Diameters [mm]	Tolerances ^[1] on the diameters [mm]	Symalit® PVDF 1000 natural	
		Standard length per piece: [3000 mm ^[2]] [kg/pce ^[3]]	
10	+0,1 +0,5	0,45	■
16	+0,2 +0,7	1,15	■
20		1,79	■
25	+0,2 +0,9	2,78	▣
30		3,96	■
36	+0,2 +1,1	5,73	▣
40		7,02	■
45	+0,3 +1,3	8,94	▣
50		10,98	■
60	+0,3 +1,6	15,81	■
70		21,42	▣
80	+0,4 +2,0	28,08	■
90	+0,5 +2,2	35,55	▣
100	+0,6 +2,5	43,95	■
120	+0,8 +3,5	63,45	■
140	+0,9 +3,8	86,25	□
150 ^[4]	+1,0 +4,2	99,15	■
180 ^[4]	+1,2 +5,0	142,65	▣
200 ^[4]	+1,3 +5,5	176,10	■
250 ^[4]	+1,5 +6,2	274,35	O.R.
Other standard length: [1000 mm ^[2]]			

^[1]: tolerances according to EN 15860

^[2]: tolerance on the length -0/+3%

^[3]: average production weights

^[4]: available in 1000 mm length only

■ : **standard** item [generally available from stock; bulk quantities to be manufactured to order]

▣ : **semi-standard** item [generally not available from stock, minimum order quantity 1 piece]

□ : **non-standard** item [generally not available from stock, manufactured to order and subject to special conditions; improved availability possible upon customer planning]

O.R.: available on request: please check for lead-time and minimum quantity

HP [High Purity] on request