

## TECHTRON® HPV PPS



POLYPHENYLENE SULFIDE [PPS]

Techtron® HPV PPS

ROUND RODS			
Diameters [mm]	Tolerances on the diameters [mm]	Techtron® HPV PPS	
		Standard length per piece: [3000 mm <sup>[1]</sup> ] [kg/pce <sup>[2]</sup> ]	
8		0,24	□
10	+0,1 +0,5	<b>0,37</b>	■
12		0,55	□
15		0,84	□
16	+0,2 +0,9	<b>0,95</b>	■
18		1,19	□
20		<b>1,46</b>	■
22		1,79	□
25		<b>2,30</b>	■
28	+0,2 +1,2	2,85	□
30		<b>3,27</b>	■
32		3,69	□
36		<b>4,71</b>	■
40	+0,2 +1,6	<b>5,79</b>	■
45		7,38	□
50	+0,3 +2,0	<b>9,06</b>	■
56		11,31	□
60		<b>13,05</b>	■
65	+0,3 +2,5	15,27	□
70		17,64	□
75		20,37	□
80	+0,4 +3,0	<b>23,10</b>	■
90	+0,5 +3,4	29,25	□
100	+0,6 +3,8	<b>36,15</b>	■
110	+0,7 +4,2	44,10	□
120	+0,8 +4,6	52,65	□
125		56,85	□
130	+0,9 +5,4	61,95	□
Other standard length: [1000 mm <sup>[1][3]</sup> ]			

<sup>[1]</sup>: tolerance on the length -0/+3%

<sup>[2]</sup>: average production weights

<sup>[3]</sup>: non-standard length for diameters over 60 mm

■ : **standard** item [generally available from stock; bulk quantities to be manufactured to order]

▣ : **semi-standard** item [generally not available from stock, minimum order quantity 1 piece]

□ : **non-standard** item [generally not available from stock, manufactured to order and subject to special conditions; improved availability possible upon customer planning]